



## SILKOLENE CHAIN LUBE

Synthetic technology motorcycle chain lubricant

### Description

An advanced synthetic technology chain lubricant specially designed for high performance motorcycle chains, resistant to high speed fling off and providing outstanding wear protection. Silkolene Chain Lube effectively penetrates the inner rollers and pins, seals the chain to combat the ingress of water and other contaminants thus increasing chain and sprocket life. Silkolene Chain Lubricant is quick drying, forms a strong thin oil film and provides good corrosion protection.

Suitable for all chains including "O", "X" and "Z" ring types.

### Advantages/Benefits

- Good antiwear and shock loading performance
- Good resistance to high speed fling off
- Resistant to water wash off
- Penetrates and evaporates quickly with excellent film forming properties
- Thin film formation resists dirt adhesion
- Good corrosion protection.

### Application

- Ensure chain is clean and dry prior to applying SILKOLENE CHAIN LUBE
- Fuchs Silkolene strongly recommends the use of SILKOLENE BRAKE AND CHAIN CLEANER prior to use
- Shake can well before application
- Apply sparingly to the whole length of the inside of a clean warm chain
- Leave for 30 minutes before use
- Wipe away excess
- Following application, invert the can and spray for a few seconds to avoid clogging the nozzle

PI60203e, PMA, 03.09.2018



**Silkolene**<sup>®</sup>  
SUPERIOR MOTORCYCLE OILS

**TECHNICAL DATA**

The information contained in this product information is based on the experience and know-how of FUCHS SCHMIERSTOFFE GMBH in the development and manufacturing of lubricants and represents the current state-of-the-art. The performance of our products can be influenced by a series of factors, especially the specific use, the method of application, the operational environment, component pre-treatment, possible external contamination, etc. For this reason, universally-valid statements about the function of our products are not possible. Our products must not be used in aircrafts/spacecrafts or their components, unless such products are removed before the components are assembled into the aircraft/spacecraft. The information given in this product information represents general, non-binding guidelines. No warranty expressed or implied is given concerning the properties of the product or its suitability for any given application.

We therefore recommend that you consult a FUCHS SCHMIERSTOFFE GMBH application engineer to discuss application conditions and the performance criteria of the products before the product is used. It is the responsibility of the user to test the functional suitability of the product and to use it with the corresponding care.

Our products undergo continuous improvement. We therefore retain the right to change our product program, the products, and their manufacturing processes as well as all details of our product information sheets at any time and without warning, unless otherwise provided in customer-specific agreements. With the publication of this product information, all previous editions cease to be valid.

Any form of reproduction requires express prior written permission from FUCHS SCHMIERSTOFFE GMBH.

© FUCHS SCHMIERSTOFFE GMBH. All rights reserved.