

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name : Shell Spirax S4 TX
Product code : 001D8247

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Substance/Mixture : Hydraulic oil, Transmission oil.
Uses advised against :
This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the supplier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : **Skeljungur hf**
Borgartún 26
105 Reykjavík
Telephone : +354 (444) 3000
Telefax :
Email Contact for Safety Data Sheet : msds@skeljungur.is

1.4 Emergency telephone number :
Emergency Line: Ambulance, Fire Department and Police,
Phone 112
; Toxic Center of the National University Hospital Phone: 543-2222

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 : H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms : No Hazard Symbol required

Signal word : No signal word

Hazard statements :
PHYSICAL HAZARDS:
Not classified as a physical hazard

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

according to CLP criteria.

HEALTH HAZARDS:

Not classified as a health hazard under CLP criteria.

ENVIRONMENTAL HAZARDS:

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.
Response:
No precautionary phrases.
Storage:
No precautionary phrases.
Disposal:
P501 Dispose of contents/ container to an approved waste disposal plant.

Sensitising components : Contains calcium sulphonate.
Contains borated ester.
Contains Triphenyl phosphite.
May produce an allergic reaction.

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis.

Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : Highly refined mineral oil.
Synthetic base oil and additives.
The highly refined mineral oil contains <3% (w/w) DMSO-extract, according to IP346.

: * contains one or more of the following CAS-numbers (REACH registration numbers): 64742-53-6 (01-2119480375-34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34), 72623-86-0 (01-2119474878-16), 72623-87-1 (01-2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-9 (01-0000020163-82), 68649-12-7 (01-2119527646-33),

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

151006-60-9 (01-2119523580-47), 163149-28-8 (01-2119543695-30).

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Interchangeable low viscosity base oil (<20,5 cSt @40°C) *		Asp. Tox.1; H304	0 - 90
Zinc dialkyldithiophosphate	4259-15-8 224-235-5	Eye Dam.1; H318 Aquatic Chronic2; H411	1 - 2,49
Calcium alkaryl sulphonate	939-141-6	Skin Sens.1B; H317	0,1 - 0,9
Borated ester	939-580-3	Skin Sens.1B; H317	0,1 - 0,9
Triphenyl phosphite	101-02-0 202-908-4	Acute Tox.4; H302 Skin Irrit.2; H315 Skin Sens.1; H317 Eye Irrit.2; H319 Aquatic Acute1; H400 Aquatic Chronic1; H410 STOT RE2; H373	0,1 - 0,24

Remarks : ** polymer exempt.

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.
If symptoms persist, obtain medical advice.

In case of skin contact : Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available.
If persistent irritation occurs, obtain medical attention.

When using high pressure equipment, injection of product

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop.
Obtain medical attention even in the absence of apparent wounds.

In case of eye contact : Flush eye with copious quantities of water.
Remove contact lenses, if present and easy to do. Continue rinsing.
If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms : Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas.
Ingestion may result in nausea, vomiting and/or diarrhoea.

Local necrosis is evidenced by delayed onset of pain and tissue damage a few hours following injection.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:
Treat symptomatically.

High pressure injection injuries require prompt surgical intervention and possibly steroid therapy, to minimise tissue damage and loss of function.
Because entry wounds are small and do not reflect the seriousness of the underlying damage, surgical exploration to determine the extent of involvement may be necessary. Local anaesthetics or hot soaks should be avoided because they can contribute to swelling, vasospasm and ischaemia. Prompt surgical decompression, debridement and evacuation of foreign material should be performed under general anaesthetics, and wide exploration is essential.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing media : Do not use water in a jet.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

(smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

- Special protective equipment for firefighters : Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to relevant Standards (e.g. Europe: EN469).
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

- Personal precautions : 6.1.1 For non emergency personnel:
Avoid contact with skin and eyes.
6.1.2 For emergency responders:
Avoid contact with skin and eyes.

6.2 Environmental precautions

- Environmental precautions : Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

6.3 Methods and materials for containment and cleaning up

- Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet.,
For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

- General Precautions : Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.

7.1 Precautions for safe handling

- Advice on safe handling : Avoid prolonged or repeated contact with skin.
Avoid inhaling vapour and/or mists.
When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Properly dispose of any contaminated rags or cleaning materials in order to prevent fires.
- Product Transfer : Proper grounding and bonding procedures should be used during all bulk transfer operations to avoid static accumulation.

7.2 Conditions for safe storage, including any incompatibilities

- Other data : Keep container tightly closed and in a cool, well-ventilated place. Use properly labeled and closable containers.
- Store at ambient temperature.
- Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.
- Packaging material : Suitable material: For containers or container linings, use mild steel or high density polyethylene.
Unsuitable material: PVC.
- Container Advice : Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

7.3 Specific end use(s)

- Specific use(s) : Not applicable

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral		TWA (Particles (mist))	1 mg/m ³	IS OEL
Further information	When certain oils are heated, polycyclic aromatic hydrocarbons (PAH) are produced which can have a carcinogenic effect. Such substances can			

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

	also be present in mineral oils., For mist from aqueous cutting fluid or suchlike, which may also include substances other than oils, the value is applied as a total content with regard to the non-aqueous part. For substances with individual lower limit values, these are applied.			
Oil mist, mineral		TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA (Mist)	1 mg/m3	IS OEL

Biological occupational exposure limits

No biological limit allocated.

Monitoring Methods

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods <http://www.cdc.gov/niosh/>

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods <http://www.osha.gov/>

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances <http://www.hse.gov.uk/>

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany <http://www.dguv.de/inhalt/index.jsp>

L'Institut National de Recherche et de Sécurité, (INRS), France <http://www.inrs.fr/accueil>

8.2 Exposure controls

Engineering measures The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned.

Practice good housekeeping.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes, protective eyewear is recommended.
Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves. Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection : Skin protection is not ordinarily required beyond standard work clothes.
It is good practice to wear chemical resistant gloves.

Respiratory protection : No respiratory protection is ordinarily required under normal conditions of use.
In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an appropriate combination of mask and filter. Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)] meeting EN14387 and EN143.

Thermal hazards : Not applicable

Environmental exposure controls

General advice : Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water. Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing vapour.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance : Liquid at room temperature.

Colour : amber

Odour : Slight hydrocarbon

Odour Threshold : Data not available

pH : Not applicable

pour point : -36 °C Method: ISO 3016

Initial boiling point and boiling range : > 280 °C Estimated value(s)

Flash point : 220 °C
Method: ISO 2592

Evaporation rate : Data not available

Flammability (solid, gas) : Data not available

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Upper explosion limit	: Typical 10 %(V)
Lower explosion limit	: Typical 1 %(V)
Vapour pressure	: < 0,5 Pa (20 °C) estimated value(s)
Relative vapour density	: > 1 estimated value(s)
Relative density	: 0,850 (15 °C)
Density	: 850 kg/m ³ (15,0 °C) Method: ISO 12185
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: Data not available
Partition coefficient: n-octanol/water	: log Pow: > 6(based on information on similar products)
Auto-ignition temperature	: > 320 °C
Decomposition temperature	: Data not available
Viscosity	
Viscosity, dynamic	: Data not available
Viscosity, kinematic	: 85 mm ² /s (40,0 °C) Method: ISO 3104
	14,1 mm ² /s (100 °C) Method: ISO 3104
Explosive properties	: Not classified
Oxidizing properties	: Data not available

9.2 Other information

Conductivity : This material is not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

10.6 Hazardous decomposition products

Hazardous decomposition products : No decomposition if stored and applied as directed.

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Basis for assessment : Information given is based on data on the components and the toxicology of similar products. Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).

Information on likely routes of exposure : Skin and eye contact are the primary routes of exposure although exposure may occur following accidental ingestion.

Acute toxicity

Product:

Acute oral toxicity : LD50 rat: > 5.000 mg/kg
Remarks: Low toxicity:
Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute dermal toxicity : LD50 Rabbit: > 5.000 mg/kg
Remarks: Low toxicity:
Based on available data, the classification criteria are not met.

Skin corrosion/irritation

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Product:

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis., Based on available data, the classification criteria are not met.

Serious eye damage/eye irritation

Product:

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not met.

Components:

Zinc dialkyldithiophosphate:

Remarks: Based on available data, the classification criteria are not met.

Respiratory or skin sensitisation

Product:

Remarks: For respiratory and skin sensitisation:, Not a sensitiser., Based on available data, the classification criteria are not met.

Components:

Borated ester:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Triphenyl phosphite:

Remarks: May cause an allergic skin reaction in sensitive individuals.

Germ cell mutagenicity

Product:

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Remarks: Product contains mineral oils of types shown to be non-carcinogenic in animal skin-painting studies., Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC).

Material	GHS/CLP Carcinogenicity Classification
-----------------	---

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Highly refined mineral oil	No carcinogenicity classification.
Triphenyl phosphite	No carcinogenicity classification.

Reproductive toxicity

Product:

:
Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Remarks: Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Not an aspiration hazard.

Further information

Product:

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: High pressure injection of product into the skin may lead to local necrosis if the product is not surgically removed.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity-
Assessment : This product does not meet the criteria for classification in categories 1A/1B.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

- Carcinogenicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.
- Reproductive toxicity - Assessment : This product does not meet the criteria for classification in categories 1A/1B.

SECTION 12: Ecological information

12.1 Toxicity

- Basis for assessment : Ecotoxicological data have not been determined specifically for this product.
Information given is based on a knowledge of the components and the ecotoxicology of similar products.
Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s). (LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test extract).

Product:

- Toxicity to fish (Acute toxicity) : Remarks: LL/EL/IL50 10-100 mg/l Harmful
- Toxicity to crustacean (Acute toxicity) : Remarks: LL/EL/IL50 10-100 mg/l Harmful
- Toxicity to algae/aquatic plants (Acute toxicity) : Remarks: LL/EL/IL50 10-100 mg/l Harmful
- Toxicity to fish (Chronic toxicity) : Remarks: NOEC/NOEL > 10 - <=100 mg/l
- Toxicity to crustacean (Chronic toxicity) : Remarks: NOEC/NOEL > 10 - <=100 mg/l
- Toxicity to microorganisms (Acute toxicity) : Remarks: NOEC/NOEL > 10 - <=100 mg/l

Components:

Triphenyl phosphite :

- M-Factor (Short-term (acute) aquatic hazard) : 1

12.2 Persistence and degradability

Product:

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Biodegradability : Remarks: Not readily biodegradable., Major constituents are inherently biodegradable, but contains components that may persist in the environment.

12.3 Bioaccumulative potential

Product:

Bioaccumulation : Remarks: Contains components with the potential to bioaccumulate.

Partition coefficient: n-octanol/water : log Pow: > 6Remarks: (based on information on similar products)

12.4 Mobility in soil

Product:

Mobility : Remarks: Liquid under most environmental conditions., Adsorbs to soil and has low mobility
Remarks: Floats on water.

12.5 Results of PBT and vPvB assessment

Product:

Assessment : This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

12.6 Other adverse effects

Product:

Additional ecological information : Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be released to air in any significant quantities under normal conditions of use.
Poorly soluble mixture., Causes physical fouling of aquatic organisms.
Mineral oil does not cause chronic toxicity to aquatic organisms at concentrations less than 1 mg/l.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product : Recover or recycle if possible.
It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations.
Do not dispose into the environment, in drains or in water courses

Waste product should not be allowed to contaminate soil or

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

ground water, or be disposed of into the environment.
Waste, spills or used product is dangerous waste.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional, national, and local laws and regulations.

Local legislation
Remarks : Disposal should be in accordance with applicable regional, national, and local laws and regulations.

SECTION 14: Transport information

14.1 UN number

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.2 Proper shipping name

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good
IATA : Not regulated as a dangerous good

14.5 Environmental hazards

ADR : Not regulated as a dangerous good
IMDG : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage, for special precautions which a user needs to be aware of or needs to comply with in connection with transport.

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation (Annex XIV) : Product is not subject to Authorisation under REACH.

Volatile organic compounds : 0 %

Other regulations : The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), annex XVII.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work and its amendments.

Directive 1994/33/EC on the protection of young people at work and its amendments.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth or are breastfeeding and its amendments.

The components of this product are reported in the following inventories:

EINECS : Notified with Restrictions.
TSCA : All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

REGULATION (EC) No 1272/2008
Long-term (chronic) aquatic hazard,
Category 3, H412

Classification procedure:
Expert judgement and weight of evidence
determination.

Full text of H-Statements

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox.	Acute toxicity
Aquatic Acute	Short-term (acute) aquatic hazard
Aquatic Chronic	Long-term (chronic) aquatic hazard
Asp. Tox.	Aspiration hazard
Eye Dam.	Serious eye damage
Eye Irrit.	Eye irritation
Skin Irrit.	Skin irritation
Skin Sens.	Skin sensitisation
STOT RE	Specific target organ toxicity - repeated exposure

Abbreviations and Acronyms : The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial Hygienists

ADR = European Agreement concerning the International Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances

ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council

CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut für Normung

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and Toxicology Of Chemicals

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial Chemical Substances

EL50 = Effective Loading fifty

ENCS = Japanese Existing and New Chemical Substances Inventory

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No Observed Effect Level

OE_HP V = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of Chemicals

RID = Regulations Relating to International Carriage of Dangerous Goods by Rail

SKIN_DES = Skin Designation

STEL = Short term exposure limit

TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

Further information

Training advice

:

Provide adequate information, instruction and training for operators.

Other information

:

No Exposure Scenario annex is attached to this safety data sheet. It is a non-classified mixture containing hazardous substances as detailed in Section 3; relevant information from Exposure Scenarios for the hazardous substances contained have been integrated into the core sections 1-16 of this SDS.

A vertical bar (|) in the left margin indicates an amendment from the previous version.

Sources of key data used to :

SAFETY DATA SHEET

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Spirax S4 TX

Version 4.4

Revision Date 05.06.2020

Print Date 06.06.2020

compile the Safety Data
Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.