According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

: Shell Spirax S5 ATE 75W-90 Trade name

Product code : 001D8288

# 1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the : Transmission oil.

Substance/Mixture

Uses advised against

This product must not be used in applications other than those

listed in Section 1 without first seeking the advice of the

supplier.

# 1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier : Skeljungur hf

> Borgartún 26 105 Reykjavík

Telephone +354 (444) 3000

Telefax : msds@skeljungur.is

**Email Contact for Safety Data** 

Sheet

1.4 Emergency telephone number

: Emergency Line: Ambulance, Fire Department and Police,

Phone 112

; Toxic Center of the National University Hospital Phone: 543-

2222

### **SECTION 2: Hazards identification**

# 2.1 Classification of the substance or mixture

# Classification (REGULATION (EC) No 1272/2008)

Based on available data this substance / mixture does not meet the classification criteria.

#### 2.2 Label elements

# Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms No Hazard Symbol required

Signal word No signal word

Hazard statements PHYSICAL HAZARDS:

Not classified as a physical hazard

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

> according to CLP criteria. **HEALTH HAZARDS:**

Not classified as a health hazard under CLP

criteria.

**ENVIRONMENTAL HAZARDS:** 

Not classified as environmental hazard

according to CLP criteria.

Precautionary statements Prevention:

No precautionary phrases.

Response:

No precautionary phrases.

Storage:

No precautionary phrases.

Disposal:

No precautionary phrases.

Safety data sheet available on request.

Sensitising components : Contains dialkylpolysulphide.

> Contains amine phosphate. May produce an allergic reaction.

# 2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used oil may contain harmful impurities.

Not classified as flammable but will burn.

## **SECTION 3: Composition/information on ingredients**

#### 3.2 Mixtures

Chemical nature : Synthetic base oil and additives.

Highly refined mineral oil.

The highly refined mineral oil contains <3% (w/w) DMSO-

extract, according to IP346.

The highly refined mineral oil is only present as additive

diluent.

\* contains one or more of the following CAS-numbers

(REACH registration numbers): 64742-53-6 (01-2119480375-

34), 64742-54-7 (01-2119484627-25), 64742-55-8 (01-

2119487077-29), 64742-56-9 (01-2119480132-48), 64742-65-0 (01-2119471299-27), 68037-01-4 (01-2119486452-34),

72623-86-0 (01-2119474878-16), 72623-87-1 (01-

2119474889-13), 8042-47-5 (01-2119487078-27), 848301-69-

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

> 9 (01-0000020163-82), 68649-12-7 (01-2119527646-33), 151006-60-9 (01-2119523580-47), 163149-28-8 (01-2119543695-30).

### **Hazardous components**

Chemical name	CAS-No.	Classification	Concentration
	EC-No.	(REGULATION	(% w/w)
	Registration	(EC) No	
	number	1272/2008)	
Interchangeable low		Asp. Tox.1; H304	0 - 90
viscosity base oil			
(<20,5 cSt @40°C) *			
Dialkylpolysulphide	68937-96-2	Skin Sens.1B;	1 - 5
	273-103-3	H317	
	01-2119540515-43	Aquatic Chronic3;	
		H412	
Amine phosphate		Acute Tox.4; H302	1 - 2,4
	931-384-6	Skin Sens.1; H317	
	01-2119493620-38	Eye Dam.1; H318	
		Aquatic Chronic2;	
		H411	

For explanation of abbreviations see section 16.

#### **SECTION 4: First aid measures**

#### 4.1 Description of first aid measures

Protection of first-aiders : When administering first aid, ensure that you are wearing the

appropriate personal protective equipment according to the

incident, injury and surroundings.

If inhaled : No treatment necessary under normal conditions of use.

If symptoms persist, obtain medical advice.

: Remove contaminated clothing. Flush exposed area with In case of skin contact

> water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.

In case of eye contact : Flush eye with copious quantities of water.

Remove contact lenses, if present and easy to do. Continue

rinsing.

If persistent irritation occurs, obtain medical attention.

If swallowed : In general no treatment is necessary unless large quantities

are swallowed, however, get medical advice.

## 4.2 Most important symptoms and effects, both acute and delayed

: Oil acne/folliculitis signs and symptoms may include formation **Symptoms** 

# Shell Spirax S5 ATE 75W-90

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.

# 4.3 Indication of any immediate medical attention and special treatment needed

Treatment : Notes to doctor/physician:

Treat symptomatically.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Foam, water spray or fog. Dry chemical powder, carbon

dioxide, sand or earth may be used for small fires only.

Unsuitable extinguishing : Do not use water in a jet.

media

# 5.2 Special hazards arising from the substance or mixture

Specific hazards during

firefighting

 Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

## 5.3 Advice for firefighters

Special protective equipment

for firefighters

: Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained Breathing Apparatus must be worn when approaching a fire in a confined space. Select fire fighter's clothing approved to

relevant Standards (e.g. Europe: EN469).

Specific extinguishing

methods

: Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

#### **SECTION 6: Accidental release measures**

#### 6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions : 6.1.1 For non emergency personnel:

Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.

### 6.2 Environmental precautions

Environmental precautions : Use appropriate containment to avoid environmental

contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate

4 / 19 800001007511

IS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

barriers.

Local authorities should be advised if significant spillages

cannot be contained.

### 6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Slippery when spilt. Avoid accidents, clean up immediately.

Prevent from spreading by making a barrier with sand, earth

or other containment material.

Reclaim liquid directly or in an absorbent.

Soak up residue with an absorbent such as clay, sand or other

suitable material and dispose of properly.

#### 6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

# **SECTION 7: Handling and storage**

**General Precautions** : Use local exhaust ventilation if there is risk of inhalation of

vapours, mists or aerosols.

Use the information in this data sheet as input to a risk assessment of local circumstances to help determine

appropriate controls for safe handling, storage and disposal of

this material.

#### 7.1 Precautions for safe handling

Advice on safe handling : Avoid prolonged or repeated contact with skin.

Avoid inhaling vapour and/or mists.

When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning

materials in order to prevent fires.

**Product Transfer** Proper grounding and bonding procedures should be used

during all bulk transfer operations to avoid static accumulation.

#### 7.2 Conditions for safe storage, including any incompatibilities

Other data : Keep container tightly closed and in a cool, well-ventilated

place. Use properly labeled and closable containers.

Store at ambient temperature.

Refer to section 15 for any additional specific legislation covering the packaging and storage of this product.

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

Packaging material : Suitable material: For containers or container linings, use mild

steel or high density polyethylene.

Unsuitable material: PVC.

Container Advice : Polyethylene containers should not be exposed to high

temperatures because of possible risk of distortion.

7.3 Specific end use(s)

Specific use(s) : Not applicable

# **SECTION 8: Exposure controls/personal protection**

# 8.1 Control parameters

## **Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral		TWA (Particles (mist))	1 mg/m3	IS OEL
Further information	When certain oils are heated, polycyclic aromatic hydrocarbons (PAH) are produced which can have a carcinogenic effect. Such substances can also be present in mineral oils., For mist from aqueous cutting fluid or suchlike, which may also include substances other than oils, the value is applied as a total content with regard to the non-aqueous part. For substances with individual lower limit values, these are applied.			
Oil mist, mineral		TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA (Mist)	1 mg/m3	IS OEL

#### **Biological occupational exposure limits**

No biological limit allocated.

#### **Monitoring Methods**

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.

Validated exposure measurement methods should be applied by a competent person and samples analysed by an accredited laboratory.

Examples of sources of recommended exposure measurement methods are given below or contact the supplier. Further national methods may be available.

National Institute of Occupational Safety and Health (NIOSH), USA: Manual of Analytical Methods http://www.cdc.gov/niosh/

Occupational Safety and Health Administration (OSHA), USA: Sampling and Analytical Methods http://www.osha.gov/

Health and Safety Executive (HSE), UK: Methods for the Determination of Hazardous Substances

# Shell Spirax S5 ATE 75W-90

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

http://www.hse.gov.uk/

Institut für Arbeitsschutz Deutschen Gesetzlichen Unfallversicherung (IFA) , Germany

http://www.dguv.de/inhalt/index.jsp

L'Institut National de Recherche et de Securité, (INRS), France http://www.inrs.fr/accueil

## 8.2 Exposure controls

**Engineering measures**The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

#### General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

### Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection : If material is handled such that it could be splashed into eyes,

protective eyewear is recommended. Approved to EU Standard EN166.

Hand protection

Remarks : Where hand contact with the product may occur the use of

gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be

replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

> gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended.

For continuous contact we recommend gloves with breakthrough time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.

Skin and body protection

Skin protection is not ordinarily required beyond standard

work clothes.

It is good practice to wear chemical resistant gloves.

Respiratory protection

No respiratory protection is ordinarily required under normal conditions of use.

In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.

If engineering controls do not maintain airborne

concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation. Check with respiratory protective equipment suppliers. Where air-filtering respirators are suitable, select an

appropriate combination of mask and filter.

Select a filter suitable for combined particulate/organic gases and vapours [Type A/Type P boiling point > 65°C (149°F)]

meeting EN14387 and EN143.

Thermal hazards : Not applicable

### **Environmental exposure controls**

General advice

: Take appropriate measures to fulfill the requirements of relevant environmental protection legislation. Avoid contamination of the environment by following advice given in Section 6. If necessary, prevent undissolved material from being discharged to waste water. Waste water should be treated in a municipal or industrial waste water treatment plant before discharge to surface water.

Local guidelines on emission limits for volatile substances must be observed for the discharge of exhaust air containing

vapour.

# Shell Spirax S5 ATE 75W-90

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

# **SECTION 9: Physical and chemical properties**

#### 9.1 Information on basic physical and chemical properties

**Appearance** : Liquid at room temperature.

Colour : amber

Odour Threshold : Data not available Hq : Not applicable

: -45 °CMethod: ISO 3016 pour point

Initial boiling point and boiling : > 280 °Cestimated value(s)

range

Flash point : 205 °C

Method: ISO 2592

Evaporation rate : Data not available Flammability (solid, gas) : Data not available

Upper explosion limit : Typical 10 %(V)

Lower explosion limit : Typical 1 %(V)

: < 0,5 Pa (20 °C) Vapour pressure

estimated value(s)

Relative vapour density : > 1estimated value(s)

Relative density : 0,879 (15 °C)

: 879 kg/m3 (15,0 °C) Density

Method: ISO 12185

Solubility(ies)

Water solubility : negligible

Solubility in other solvents : Data not available

Partition coefficient: n-

octanol/water

: log Pow: > 6(based on information on similar products)

Auto-ignition temperature

320 °C

: Data not available Decomposition temperature

Viscosity

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

Viscosity, dynamic : Data not available Viscosity, kinematic : 81 mm2/s (40,0 °C)

Method: ISO 3104

14,9 mm2/s (100 °C) Method: ISO 3104

Explosive properties : Not classified

Oxidizing properties : Data not available

9.2 Other information

Conductivity : This material is not expected to be a static accumulator.

# **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

# 10.2 Chemical stability

Stable.

No hazardous reaction is expected when handled and stored according to provisions

#### 10.3 Possibility of hazardous reactions

Hazardous reactions : Reacts with strong oxidising agents.

10.4 Conditions to avoid

Conditions to avoid : Extremes of temperature and direct sunlight.

10.5 Incompatible materials

Materials to avoid : Strong oxidising agents.

### 10.6 Hazardous decomposition products

Hazardous decomposition

products

: No decomposition if stored and applied as directed.

# **SECTION 11: Toxicological information**

### 11.1 Information on toxicological effects

Basis for assessment : Information given is based on data on the components and

the toxicology of similar products. Unless indicated otherwise,

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

the data presented is representative of the product as a

whole, rather than for individual component(s).

exposure

Information on likely routes of : Skin and eye contact are the primary routes of exposure

although exposure may occur following accidental ingestion.

### **Acute toxicity**

# **Product:**

: LD50 rat: > 5.000 mg/kg Acute oral toxicity

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

: Remarks: Based on available data, the classification criteria Acute inhalation toxicity

are not met.

: LD50 Rabbit: > 5.000 mg/kg Acute dermal toxicity

Remarks: Low toxicity:

Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

#### **Product:**

Remarks: Slightly irritating to skin., Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.. Based on available data, the classification criteria are not met.

#### Serious eye damage/eye irritation

# **Product:**

Remarks: Slightly irritating to the eye., Based on available data, the classification criteria are not

#### Components:

#### Amine phosphate:

Remarks: Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

# **Product:**

Remarks: For respiratory and skin sensitisation:, Not a sensitiser., Based on available data, the classification criteria are not met.

#### Components:

### Dialkylpolysulphide:

Remarks: Experimental data has shown that the concentration of potentially sensitising

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

components present in this product does not induce skin sensitisation., May cause an allergic skin reaction in sensitive individuals.

## Amine phosphate:

Remarks: Experimental data has shown that the concentration of potentially sensitising components present in this product does not induce skin sensitisation., May cause an allergic skin reaction in sensitive individuals.

# Germ cell mutagenicity

## **Product:**

: Remarks: Non mutagenic, Based on available data, the classification criteria are not met.

# Carcinogenicity

### **Product:**

Remarks: Not a carcinogen., Based on available data, the classification criteria are not met.

Material	GHS/CLP Carcinogenicity Classification
Highly refined mineral oil	No carcinogenicity classification.

# Reproductive toxicity

#### **Product:**

Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria are not met.

#### STOT - single exposure

## **Product:**

Remarks: Based on available data, the classification criteria are not met.

# STOT - repeated exposure

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

# **Aspiration toxicity**

# **Product:**

Not an aspiration hazard.

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

#### **Further information**

#### **Product:**

Remarks: Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal., ALL used oil should be handled with caution and skin contact avoided as far as possible.

Remarks: Slightly irritating to respiratory system.

Remarks: Classifications by other authorities under varying regulatory frameworks may exist.

Summary on evaluation of the CMR properties

Germ cell mutagenicity-

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

Carcinogenicity -

Assessment

This product does not meet the criteria for classification in

categories 1A/1B.

Reproductive toxicity -

Assessment

: This product does not meet the criteria for classification in

categories 1A/1B.

# **SECTION 12: Ecological information**

## 12.1 Toxicity

: Ecotoxicological data have not been determined specifically Basis for assessment

for this product.

Information given is based on a knowledge of the components

and the ecotoxicology of similar products.

Unless indicated otherwise, the data presented is representative of the product as a whole, rather than for individual component(s).(LL/EL/IL50 expressed as the nominal amount of product required to prepare aqueous test

extract).

Product:

Toxicity to fish (Acute

toxicity)

: Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to crustacean (Acute

toxicity)

: Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

Toxicity to algae/aquatic plants (Acute toxicity)

: Remarks: LL/EL/IL50 > 100 mg/l

Practically non toxic:

Based on available data, the classification criteria are not met.

Toxicity to fish (Chronic

toxicity)

: Remarks: Data not available

: Remarks: Data not available

Toxicity to crustacean (Chronic toxicity)

Toxicity to microorganisms

(Acute toxicity)

Remarks: Data not available

## 12.2 Persistence and degradability

### **Product:**

Biodegradability : Remarks: Not readily biodegradable., Major constituents are

inherently biodegradable, but contains components that may

persist in the environment.

# 12.3 Bioaccumulative potential

# **Product:**

Bioaccumulation : Remarks: Contains components with the potential to

bioaccumulate.

Partition coefficient: n-

octanol/water

: log Pow: > 6Remarks: (based on information on similar

products)

# 12.4 Mobility in soil

# **Product:**

Mobility : Remarks: Liquid under most environmental conditions., If it

enters soil, it will adsorb to soil particles and will not be

mobile.

Remarks: Floats on water.

#### 12.5 Results of PBT and vPvB assessment

#### **Product:**

Assessment : This mixture does not contain any REACH registered

substances that are assessed to be a PBT or a vPvB.

#### 12.6 Other adverse effects

#### **Product:**

Additional ecological

information

: Does not have ozone depletion potential, photochemical ozone creation potential or global warming potential., Product is a mixture of non-volatile components, which will not be

released to air in any significant quantities under normal conditions of use.

Poorly soluble mixture., Causes physical fouling of aquatic

organisms.

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

# **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Product : Recover or recycle if possible.

It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water

courses

Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Contaminated packaging : Dispose in accordance with prevailing regulations, preferably

to a recognized collector or contractor. The competence of the collector or contractor should be established beforehand. Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

Local legislation

Remarks : Disposal should be in accordance with applicable regional,

national, and local laws and regulations.

# **SECTION 14: Transport information**

14.1 UN number

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.2 Proper shipping name

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.3 Transport hazard class

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

14.4 Packing group

ADR : Not regulated as a dangerous good IMDG : Not regulated as a dangerous good IATA : Not regulated as a dangerous good

#### 14.5 Environmental hazards

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

ADR : Not regulated as a dangerous good : Not regulated as a dangerous good

14.6 Special precautions for user

Remarks : Special Precautions: Refer to Section 7, Handling & Storage,

for special precautions which a user needs to be aware of or

needs to comply with in connection with transport.

### 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied. MARPOL Annex 1 rules apply for bulk shipments by sea.

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - List of substances subject to authorisation : Product is not subject to (Annex XIV) : Authorisation under REACH.

Volatile organic compounds : 0 %

Other regulations : The regulatory information is not intended to be

comprehensive. Other regulations may apply to this material.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH), annex XIV.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of

Chemicals (REACH), annex XVII.

Directive 2004/37/EC on the protection of workers from the risks related to exposure to carcinogens or mutagens at work

and its amendments.

Directive 1994/33/EC on the protection of young people at

work and its amendments.

Council Directive 92/85/EEC on the introduction of measures to encourage improvements in the safety and health at work of pregnant workers and workers who have recently given birth

or are breastfeeding and its amendments.

#### The components of this product are reported in the following inventories:

EINECS : Not established. TSCA : All components listed.

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

#### 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

#### **SECTION 16: Other information**

,

#### Full text of H-Statements

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H317 May cause an allergic skin reaction. H318 Causes serious eye damage.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

#### Full text of other abbreviations

Acute Tox. Acute toxicity

Aquatic Chronic Long-term (chronic) aquatic hazard

Asp. Tox. Aspiration hazard
Eye Dam. Serious eye damage
Skin Sens. Skin sensitisation

Abbreviations and Acronyms

 The standard abbreviations and acronyms used in this document can be looked up in reference literature (e.g. scientific dictionaries) and/or websites.

ACGIH = American Conference of Governmental Industrial

Hygienists

ADR = European Agreement concerning the International

Carriage of Dangerous Goods by Road

AICS = Australian Inventory of Chemical Substances ASTM = American Society for Testing and Materials

BEL = Biological exposure limits

BTEX = Benzene, Toluene, Ethylbenzene, Xylenes

CAS = Chemical Abstracts Service

CEFIC = European Chemical Industry Council CLP = Classification Packaging and Labelling

COC = Cleveland Open-Cup

DIN = Deutsches Institut fur Normung
DMEL = Derived Minimal Effect Level
DNEL = Derived No Effect Level

DSL = Canada Domestic Substance List

EC = European Commission

EC50 = Effective Concentration fifty

ECETOC = European Center on Ecotoxicology and

**Toxicology Of Chemicals** 

ECHA = European Chemicals Agency

EINECS = The European Inventory of Existing Commercial

Chemical Substances

EL50 = Effective Loading fifty

**ENCS** = Japanese Existing and New Chemical Substances

Inventory

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

EWC = European Waste Code

GHS = Globally Harmonised System of Classification and

Labelling of Chemicals

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IC50 = Inhibitory Concentration fifty

IL50 = Inhibitory Level fifty

IMDG = International Maritime Dangerous Goods

INV = Chinese Chemicals Inventory

IP346 = Institute of Petroleum test method N° 346 for the determination of polycyclic aromatics DMSO-extractables

KECI = Korea Existing Chemicals Inventory

LC50 = Lethal Concentration fifty

LD50 = Lethal Dose fifty per cent.

LL/EL/IL = Lethal Loading/Effective Loading/Inhibitory loading

LL50 = Lethal Loading fifty

MARPOL = International Convention for the Prevention of

Pollution From Ships

NOEC/NOEL = No Observed Effect Concentration / No

Observed Effect Level

OE\_HPV = Occupational Exposure - High Production Volume

PBT = Persistent, Bioaccumulative and Toxic

PICCS = Philippine Inventory of Chemicals and Chemical

Substances

PNEC = Predicted No Effect Concentration

REACH = Registration Evaluation And Authorisation Of

Chemicals

RID = Regulations Relating to International Carriage of

Dangerous Goods by Rail
SKIN\_DES = Skin Designation
STEL = Short term exposure limit
TRA = Targeted Risk Assessment

TSCA = US Toxic Substances Control Act

TWA = Time-Weighted Average

vPvB = very Persistent and very Bioaccumulative

# **Further information**

Training advice

Provide adequate information, instruction and training for

operators.

Other information : N

: No Exposure Scenario annex is attached to this safety data sheet. It is a non-classified mixture containing hazardous substances as detailed in Section 3; relevant information from Exposure Scenarios for the hazardous substances contained have been integrated into the core sections 1-16 of this SDS.

A vertical bar (|) in the left margin indicates an amendment

from the previous version.

According to EC No 1907/2006 as amended as at the date of this SDS

# **Shell Spirax S5 ATE 75W-90**

Version 2.5 Revision Date 10.07.2020 Print Date 11.07.2020

Sources of key data used to compile the Safety Data Sheet

The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU

IUCLID date base, EC 1272 regulation, etc).

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.