

BB00.40-P-0231-02A	Specified transmission oils (commercial vehicle, van) - Overview		
--------------------	--	--	--

These tables serve only as an overview!

- Should be used.
- Can be used.



With conversion to another oil:

Change service life factors in the maintenance system (WS) and pay attention to specified service interval processors.

Note:

For commercial vehicle axle applications in the service fill area 235.6 can be used equivalently to 235.0.

Commercial vehicles, vans - axles, sheets 235.0 up to 235.31								
Major assembly		Sheet No. 235						
		.0	.1	.5	.6	.8	.20	.31
	SAE grade		80, 80W, 80W/85 W	80, 80W, 80W/85 W		75W-90, 80W-90	75W-90, 80W-90	75W-85
			Hot zones 90, 85W-90	Hot zones 90, 85W-90		85W-90, 90	85W-90, 90	
Hypoid differential D741.160, D746.209/305, D746.301/302 (tandem), D746.301 (solo drive) up to 12/2013, D748.595						•	○1.)	
Hypoid differential D746.301 (solo drive) as of 01/2014							○1.)	•
all other hypoid differentials		○			○	•	•	
Planetary axle		○			○	•	•	
Pinion shaft			•	•				
Hypoid differential D741.161/421/422/423/453/454/455						○		•