

## KABI Electric pump kit for AdBlue® Incl. automatic nozzle with built-in digitalflow meter and bracket for IBC container



KABI

## Description

Complete AdBlue® pump kit with Automatic nozzle with builtin digital flow meter. Self-priming diaphragm pump with continuous operating time. 6 meter antistatic hose is divided as needed for suction and discharge. SEC coupling for suction pipe and swivel adapter for suction from bottom valve are both included in the set as standard. The pump is suitable for pumping AdBlue, coolant, other liquids and water. (not drinking water)

## **Specifications**

Art.#	43430
Brand	KABI
Pump capacity	35 ltr./min.
Lift height	Max. 8,0 mtr
IP Class	55
Duty cycle	Continuously
Power cable	4 mtr.
Pump specifications	Self-priming with by-pass.
With	Diaphragm pump, Nozzle, 6 meter hose, SEC coupling for suction pipe, DIN61 swivel adapter for bottom valve, stainless bracket for IBC tank, plastic holder for nozzle and misc. fittings.
Working pressure	Max. 1,2 bar.
Working pressure Noise level	Max. 1,2 bar. 70 dB
	·
Noise level	70 dB
Noise level Material	70 dB EPDM membrane
Noise level Material Motor	70 dB EPDM membrane 0,45HK - 2850 rpm./min.
Noise level Material Motor Hose connection	70 dB EPDM membrane 0,45HK - 2850 rpm./min. 3/4
Noise level Material Motor Hose connection Volt	70 dB   EPDM membrane   0,45HK - 2850 rpm./min.   3/4   230V AC - 1,5Amp
Noise levelMaterialMotorHose connectionVoltMax. fluid temperature	70 dB   EPDM membrane   0,45HK - 2850 rpm./min.   3/4   230V AC - 1,5Amp   -5°C / max. +40°C.

