

TDS

VENOL ATF CVT TRANSMISSION

1.PRODUCT CHARACTERISTICS:

Gear oil intended for automatic transmission CVT type. It guarantees exceptional protection even in the most difficult transmission conditions and meets all the requirements of CVT gearboxes. Provides excellent wear protection throughout the entire service life, increases foaming resistance and guarantees resistance to deposit formation. The use of ATF CVT oil as a substitute for other ATF oils is not recommended. Ready to be mixed with other branded gear oils of this kind.

2. SPECIFICATIONS:

[✓] ISO VG: 32

3. MEETS THE REQUIREMENTS:

VW/AUDI TL 52180/G 052 180; FORD CVT 23/CVT 30; MERCON C; HONDA HMMF; TOYOTA TC; NISSAN NS-1, NS-2, NS-3; MITSUBISHI CVTF-J1/SP-III; SUBARU NS-2/LINEARTRONIC CVTF; MINI COOPER EZL 799; HYUNDAI GENUINE CVTF; HYUNDAI/KIA SP-III; SUZUKI TC/NS-2/CVT GREEN 1; DODGE/JEEP NS-2/CVTF +4; GM/SATURN DEX-CVT

4. TECHNICAL REQUIREMENTS:

VENOL ATF CVT TRANSMISSION	Typical values
Kinematic viscosity at 40° C mm ² /s	31
Viscosity index	172
Pour point ⁰ C, max ⁰ C	-48
Flash point ^o C	220

Venol Motor Oil GmbH Litauische Str. 43 15234 Frankfurt Oder Ust-Id- Nr DE-319472195 ST-NR 061/121/03730 HRB 93818 Geschäftsführer: Maciej Filip Gostynski Bankverbindung: DE 38 4401 0046 0408 0114 61 BIC: PBNKDEFF Tel. 0049 335 401 44 01 venol@venol.pl



Venol Motor Oil GmbH Litauische Str. 43 15234 Frankfurt Oder Ust-Id- Nr DE-319472195 ST-NR 061/121/03730 HRB 93818

Geschäftsführer: Maciej Filip Gostynski Bankverbindung: DE 38 4401 0046 0408 0114 61 BIC: PBNKDEFF Tel. 0049 335 401 44 01 venol@venol.pl

www.venol.de