

Product Information VG.40.01

30-05-2022

VatOil UTTO 68

Description

UTTO 68 is a modern, universal hydraulic and transmission fluid. The special formulation with high quality solvent refined base oils and selected additives gives the product the following properties:

- Very high and stable viscosity index
- Very low pouring point
- Very good stability against oxidation
- Good 'Extreme Pressure'- and anti-wear properties
- For use in systems with 'wet' brakes
- Excellent anti-rust and anti-corrosion properties

Application

UTTO 68 (Universal Tractor Transmission Oil) is suitable for the hydraulics and transmission systems of almost all tractors and other agricultural equipment. Always check the product recommendation database for the right application.

Specifications

API GL-4

Allison C4

Case MS1206/MS1207/MS1209

Cat TO-2

Ford M2C134-D

John Deere J20C

Massey Ferguson M1135/M1143

NH 410B

Volvo WB 101

ZF TE-ML 03E/05F/06K

Typicals

| | |
|--------------------------------------|---------|
| Density at 15 °C, kg/l | 0,881 |
| Viscosity -20 °C, mPa.s | 4000 |
| Viscosity 40 °C, mm ² /s | 67,00 |
| Viscosity 100 °C, mm ² /s | 10,60 |
| Viscosity Index | 147 |
| Flash Point COC, °C | 225 |
| Pour Point, °C | -39 |
| Total Base Number, mgKOH/g | 7,3 |
| Sulphate Ash, % | 1,19 |
| Noack, % | 12,2 |
| Brookfield -40°C, mPa.s | >900000 |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Available packagings50187
20 L can50188
60 L drum50189
210 L drum