



## VENOL VENLUB L HM L HLP

### 1. PRODUCT CHARACTERISTICS:

Hydraulic oils with increased anti-wear properties. Intended for use in hydraulic power transmission systems and control systems. This oils have excellent anti-wear properties due to the presence of zinc-containing additives and properties anti-corrosive, anti-oxidation, anti-foaming and deemulsifying. This oils have very good filterability.

### 2. SPECIFICATIONS:

ISO VG: 32, 46, 68, 100, 150  
ISO: L – HM  
DIN: L – HLP  
DIN 51524 - 2

### 3. TECHNICAL REQUIREMENTS:

VENOL VENLUB L HV L HLP	LHVLHLP 32	LHVLHLP 46	LHVLHLP 68	LHVLHLP 100	LHVLHLP 150
Kinematic viscosity at 40 <sup>0</sup> C mm <sup>2</sup> /s	28,8-35,2	41,4-50,6	61,2-74,8	90-110	135-165
Viscosity index	105	105	100	95	95
Pour point, max <sup>0</sup> C	-27	-27	-27	-24	-24
Flash point, <sup>0</sup> C	210	210	210	210	210

Venol Motor Oil GmbH  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

Geschäftsführer: Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl



**Venol Motor Oil GmbH**  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl

[www.venol.de](http://www.venol.de)