



## TDS

### VENOL TRACTOR U HLP/CLP/GL-4 10W/30

#### Characteristics:

Universal hydraulic and gear oil, enriched with a composition of performance-enhancing additives with lubricating, antioxidant, anti-corrosive, anti-foaming and anti-grinding properties. Designed for use in gear and hydraulic systems, as a lubricant in the powertrain system (also with wet brakes) and as a working fluid in hydraulic systems of farm tractors and agricultural machinery.

#### Specifications and Standards:

Viscosity grade: SAE 10W/30  
Quality class: API :HLP/CLP/GL-4

**Meets the requirements:** CNH MAT 3525(MS 1209),FORD M2C 134 D,JOHN DEERE J20C, MF CMS M1135,M1143,ALLISON C-4,CATERPILLAR TO-2,ZF TE-ML 03E,05F

Venol Tractor U HLP/CLP	Typical physico-chemical attributes
Viscosity at 100°C, mm <sup>2</sup> /s	10,7
Viscosity index, min	110
Pour point, max °C	- 24
Flash point, min °C	210

Venol Motor Oil GmbH  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl



**Venol Motor Oil GmbH**  
Litauische Str. 43  
15234 Frankfurt Oder  
Ust-Id- Nr DE-319472195  
ST-NR 061/121/03730  
HRB 93818

**Geschäftsführer:** Maciej Filip Gostynski  
Bankverbindung: DE 38 4401 0046 0408 0114 61  
BIC: PBNKDEFF  
Tel. 0049 335 401 44 01  
venol@venol.pl

[www.venol.de](http://www.venol.de)