

# KABI Air-Operated Lubricator for 18-25 kg.



## Description

KABI air-operated mobile grease lubricator with pressure ratio 50:1, is designed to lubricate machinery and all mechanical equipment within the automotive, industrial, marine, farming and aircraft sectors. The lubricator **must** be supplied with mist lubrication (FRL unit) 60286.

## Specifications

<b>Art.#</b>	60442
<b>Brand</b>	KABI
<b>Pump capacity</b>	1000 g/min. with 7 bar
<b>With</b>	Air-operated grease pump, cover plate, Trolley, 2 mtr. Grease hose, Z-Swivel, High-pressure grease gun with tube and nozzle.
<b>Working pressure</b>	7 bar
<b>Pressure ratio</b>	50:1
<b>Min. pressure</b>	2 bar
<b>Max. pressure</b>	8 bar
<b>Lubrications</b>	Grease up to NLGI 2
<b>Connection (air)</b>	1/4"BSP
<b>Connection (grease)</b>	1/4"BSP
<b>Noise level</b>	81 Db.
<b>Air consumption</b>	230 l/min.
<b>Used for</b>	18 - 25 kg. Grease Bucket
<b>Cover</b>	Ø 260 – 310 mm.
<b>Pump</b>	60445
<b>Customs code (CN8)</b>	82055920
<b>EAN</b>	5708800604422