



PerfectFinish Sealant

Spray sealant for a high-gloss surface

PerfectFinish Sealant is an efficient spray sealant for the long-lasting protection of vehicle paint surfaces. The treated surface is given a high-gloss finish. PerfectFinish Sealant can be used as a stand-alone sealant. Due to its strong hydrophobicity, it is suitable as a topping for an existing ceramic coating. Follow-up vehicle washes are simplified by the easy-to-clean effect. Easy to use with a pleasant fruity fragrance.

page 1 of 1

Areas of use

Painted surfaces on cars, commercial vehicles, motorcycles, etc.

Recommendations for use

Pre-clean/wash the vehicle according to how dirty it is and dry thoroughly. Depending on the condition of the paintwork, treat the surface with a silicone-free polish and then degrease with Panel Preparation Spray. Spray PerfectFinish Sealant onto a clean Polish & Sealing Towel and spread evenly over contiguous areas. Finally, remove the residue with a dry Polish & Sealing Towel. Do not spray directly onto painted surfaces. Alternatively, the product can be applied by machine. To do this, apply PerfectFinish Sealant to a Polish & Sealing Foam Pad and work it into the vehicle paintwork in sections using a compressed air eccentric or eccentric polishing machine. Finally, remove the residue with a dry Polish & Sealing Towel. After applying PerfectFinish Sealant, the vehicle must not be washed again within 24 hours.

Container

Container	Item no.
5 L	685005
	685088
10 STK	685500

Warnings

Do not apply to heated surfaces or allow to dry. Do not use in the sun. Protect from frost. Shake before use. Check for suitability and compatibility before use. Do not use below 10 degrees ambient temperature.

Notice

This product information can advise you only without obligation. Liability on our part can not be derived. Please check whether the product is suitable for your application. We will be pleased to assist you.